

## HIGH TEMPERATURE Commercial Grade Condensate Pump PlenumPlus™ Model A3/A5



- 💧 UL 2043 Tested
- 💧 Plenum rated
- 💧 Max temperature 212°
- 💧 Rated for use with steam condensate
- 💧 Heavy duty construction

The same great pump is now plenum rated. Hartell's PlenumPlus™ Commercial Grade Condensate Pump A3/A5 has been tested to, and yielded results that fell within the acceptable criteria of UL standard 2043, Third Edition, "Fire test for heat and visible smoke release for discrete products and their accessories installed in air-handling spaces." The UL standard 2043 rating assures the PlenumPlus™ pump is an optimal choice for use in plenum spaces.

### FEATURES:

- 💧 1 Gallon, heavy-duty reservoir
- 💧 Easy wire access
- 💧 60 ft Max lift
- 💧 Includes auxiliary safety switch on all models
- 💧 Reversible reservoir allows installation flexibility
- 💧 1 year warranty

**PLENUM  
RATED**



Model	Part No.	Voltage	Performance							Max Lift	Dimensions			
			Lift / Feet	6'	12'	18'	24'	--	--		Width	Length	Height	Weight
A3X	806029 806028 806030	115V 3.1A 208/230V 1.1A 277V 1.0A	Lift / Feet	6'	12'	18'	24'	--	--	30'	6"	12"	10.5"	11lb
			Gallons / Hr	351	309	245	180	--	--					
			Lift / Meters	1.8m	3.7m	5.5m	7.3m	--	--	9m	15.24cm	30.48cm	26.67cm	5kg
			Liters / Hr	1329	1170	927	681	--	--					
A5X	806025 806026 806027	115V 6.0A 208/230V 3.3A 380/460V 1.1A	Lift / Feet	6'	12'	18'	24'	36'	48'	60'	6"	12"	10.5"	15lb
			Gallons / Hr	550	528	495	462	390	306					
			Lift / Meters	1.8m	3.7m	5.5m	7.3m	11m	15m	18m	15.24cm	30.48cm	26.67cm	6.8kg
			Liters / Hr	2082	1999	1874	1749	1476	1158					

When safety counts, you can rely on Hartell PlenumPlus™

# DATA SHEET

## HIGH TEMPERATURE Commercial Grade Condensate Pump PlenumPlus™ Model A3/A5

PLENUM  
RATED



1  
YEAR  
WARRANTY

